

ACTIFLOW MGO 500**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product name : ACTIFLOW MGO 500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use for agriculture (nutrients/ trace elements for plants)

1.3. Details of the supplier of the safety data sheet

Registered company name : AGRONUTRITION SAS..

Address : Parc Activestre - 3 avenue de l'Orchidée.31390.CARBONNE.FRANCE.

Telephone : +33 (0)5 61 97 85 00. Fax : .

fds-msds@agro-nutrition.fr

Distributed by: DeSangosse New Zealand Ltd, PO Box113Te Awamutu, 3841.Ph:07 827 4856, Fax:07 827 4806infonz@desangosse.com

1.4. Emergency telephone number : +0800 764 766.

Association/Organisation : New Zealand National Poisons Centre:poisons@otago.ac.nz.

SECTION 2 : HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture****In compliance with EC regulation No. 1272/2008 and its amendments.**

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

May produce an allergic reaction (EUH208).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS07

Signal Word :

WARNING

Product identifiers :

EC 215-170-3 HYDROXIDE DE MAGNESIUM

Additional labeling :

EUH208 Contains REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

Hazard statements :

H315

Causes skin irritation.

H319

Causes serious eye irritation.

ACTIFLOW MGO 500

H335	May cause respiratory irritation.
Precautionary statements - General :	
P102	Keep out of reach of children.
Precautionary statements - Prevention :	
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/... if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
Precautionary statements - Disposal :	
P501	Dispose of contents/ container to an approved waste disposal plant.
Other information :	
	Replace the contents / container to an approved disposal center.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 1309-42-8 EC: 215-170-3 REACH: 01-2119488756-18-xxxx HYDROXIDE DE MAGNESIUM			25 \leq x % < 50
INDEX: 613-167-00-5 CAS: 55965-84-9 REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	B	0 \leq x % < 2.5

(Full text of H-phrases: see section 16)

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

ACTIFLOW MGO 500

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/lesions after inhalation: cough, respiratory tract irritation.

Symptoms/lesions after skin contact: skin irritation, redness.

Symptoms/lesions after eye contact: corrosion, irritation of the eye tissues.

Symptoms/lesions after ingestion: abdominal pain, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Specific and immediate treatment :

symptomatic treatment

Eye bathing the scene.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

- foam

- powder

- carbon dioxide (CO₂)

The choice of the method depends on the other products present.

Do not use a strong water jet, danger of spreading of the product.

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- nitrogen oxide (NO)

- carbon monoxide (CO)

5.3. Advice for firefighters

Precautions against fire: like in case of all fires involving chemicals, wear appropriate protective equipment (chemical protective clothing, boots and gloves).

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

If spill is large, evacuate all personnel and only allow intervention by trained operators and equipped with individual protection equipment appropriate (refer to Section 8).

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

ACTIFLOW MGO 500

6.4. Reference to other sections

See section 1 for information about emergency contact.
See section 13 for obtain additional information on waste treatment.
See section 8 for information on personal protection equipments.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.
Remove and wash contaminated clothing before re-using.

Fire prevention :

Handle in well-ventilated areas.
Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.
Observe precautions stated on label and also industrial safety regulations.
Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.
Provide vapor extraction at the emission source and also general ventilation of the premises.
Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.
In all cases, recover emissions at source.
Avoid skin and eye contact with this mixture.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.
Keep the container tightly closed in a dry, well-ventilated place.
Keep away from food, drink and animal feedingstuffs.
Storage temperature: 0-35°C

Packaging

Replace the label in case of split of packaging.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.
Use eye protectors designed to protect against liquid splashes
Before handling, wear safety goggles with protective sides accordance with standard EN166.
In the event of high danger, protect the face with a face shield.
Prescription glasses are not considered as protection.
Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

ACTIFLOW MGO 500

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP2

If the setting covers the product and its application (spray atomization) is generating aerosol or fine particles liquids, it is recommended to wear a respirator, properly fitted.

Exposure controls linked to environmental protection

Do not discharge into drains, surface waters or soil. Recover accidentally quantities of common ground products. Remove waste in accordance with local and national regulations.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Fluid liquid.
Color	opaque beige
Odor	Odourless
State	Concentrated suspension (SC)

Important health, safety and environmental information

pH (aqueous solution) :	9.00 +/-0.6 (10g/l)
pH :	10.00 +/-0.6.
	Slightly basic.
Boiling point/boiling range :	Not relevant.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	1435 (+/-1.5%) g/dm ³
Water solubility :	Soluble.
Melting point/melting range :	Not relevant.
Self-ignition temperature :	Not relevant.

ACTIFLOW MGO 500

Decomposition point/decomposition range : Not relevant.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

According to our knowledge, this product does not present any particular hazard under normal conditions of use and storage.

10.4. Conditions to avoid

Avoid :

- frost
- exposure to light

10.5. Incompatible materials

Keep away from :

- strong acids
- strong oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- nitrogen oxide (NO)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

11.1.1. Substances

Acute toxicity :

HYDROXIDE DE MAGNESIUM (CAS: 1309-42-8)

Oral route : LD50 >= 5000 mg/kg
Species : Rat

11.1.2. Mixture

Acute toxicity :

No data on the product itself is available. However according to the representative components, it is possible to provide: Oral LD50 (rat) > 2000mg/kg

Skin corrosion/skin irritation :

may cause skin irritation

Repeated exposure may cause skin dryness or cracking skin.

Serious damage to eyes/eye irritation :

May cause reversible eye effects such as eye irritation

The severity depends on the concentration and exposure time

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

Germ cell mutagenicity :

No evidence of this effect was found.

Carcinogenicity :

No evidence of this effect was found

Reproductive toxicant :

No evidence of this effect was found.

ACTIFLOW MGO 500

SECTION 12 : ECOLOGICAL INFORMATION

The mineral elements (nutrients) contained in this product are essential for healthy plant growth, but may be harmful in large quantities to wildlife, aquatic organisms or sensitive plants. It is therefore necessary to minimize the amount of product released into the environment, except as part a rational fertilization program for the plants, preferably after a test for soil and/or plant issues.

12.1. Toxicity

12.1.1. Substances

HYDROXIDE DE MAGNESIUM (CAS: 1309-42-8)

Fish toxicity : LC50 > 10000 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 > 10000 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

HYDROXIDE DE MAGNESIUM (CAS: 1309-42-8)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.2.2. Mixtures

This product is considered readily biodegradable (slightly hazardous) and it is very soluble in water. Ensure that all flow not not resulted in the aquatic environment, or any sewer or drain. When using, do not spill the product beyond the cultivated areas (hedges, edges, ditches, streams).

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, VwVwS vom 27/07/2005, KBws) :

WGK 1 : Slightly hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Local arrangements :

submit to an approved disposal.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

06 03 14 solid salts and solutions other than those mentioned in 06 03 11 and 06 03 13

ACTIFLOW MGO 500

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

- Container information:

No data available.

- Particular provisions :

No data available.

Substances that deplete the ozone layer (EC Regulation No. 1005/2009, Montreal Protocol) :

This product is not subject to any regulation concerning the nomenclature of classified installations (storage and use).

- German regulations concerning the classification of hazards for water (WGK, VwVwS vom 27/07/2005, KBws) :

WGK 1 : Slightly hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

The information contained in this MSDS was obtained from sources which we believe are reliable and corresponds to the current state of our knowledge and experience of the product and is not exhaustive. This applies to product which conforms to the specifications, unless otherwise stated. In case of formulations or mixtures, make sure that no new dangers can not be produced.

The product should not be used for other purposes than those specified under section 1. Attention of users is drawn to the possible risks incurred when a product is used for purposes other than those for which it was designed, without the prior written handling instructions.

This complements the technical sheets but does not replace plug. Is not exempt under any circumstances, the product user to comply with all laws, regulations and procedures relating to the product, safety, hygiene and protection human health and the environment.

Monitoring of changes in the MSDS

review in the light of Regulation CLP (CE) 1272/2008

Wording of the phrases mentioned in section 3 :

H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark